## RECEIVED CENTRAL FAX CENTER

Serial No.: 10/810,931 Inventor(s): Masters et al.

AUG 1 4 2006

U.S. PTO Customer No. 25280

Case No.: 5709

## AMENDMENTS TO THE CLAIMS

- 1. (withdrawn) A sunscreen fabric comprising:
- a warp knit fabric having at least a two bar construction, and a polymer coating applied to said fabric, wherein said polymer coating comprises a urethane polymer and the coated fabric exhibits a cup/curl of less than about 20 mm at 96 inches of width.
- 2. (withdrawn) A fabric according to Claim 1, wherein said polymer coating is substantially transparent.
- 3. (withdrawn) A fabric according to Claim 1, wherein said fabric has an openness of about 2 to about 25%.
- 4. (withdrawn) A fabric according to Claim 1, wherein said fabric has a mark-off resistance of about 3.5 or greater.
- 5. (withdrawn) A fabric according to Claim 1, wherein said fabric further comprises a flame retardant.
- 6. (withdrawn) A fabric according to Claim 1, wherein said fabric is in the form of a window shade.
- 7. (withdrawn) A sunscreen comprising:
  - a knit fabric, and
  - a mechanism for securing said knit fabric to a structure.
- 8. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric has an openness of about 2 to about 25%.
- 9. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric is coated with a polymer, and said coated fabric exhibits a Cup/curl of about 20 mm or less over 96 inches of width.

Serial No.: 10/810,931 Inventor(s): Masters et al.

U.S. PTO Customer No. 25280 Case No.: 5709

- 10. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric is coated with a polymer, and said coated fabric exhibits a mark-off resistance of about 3.5 or greater.
- 11. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric is coated with a polymer selected from the group consisting of aliphatic polyesters, aliphatic polyethers, and combinations thereof.
- 12. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric is a warp knit fabric having at least a two bar knit construction.
- 13. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric is a warp knit fabric selected from the group consisting of tricot knit and raschel knit fabrics.
- 14. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric has an openness of about 2 to about 25% and said knit fabric is coated with a polymer, wherein said coated fabric exhibits a Cup/curl of about 20 mm or less over 96 inches of width when tested according to a Cup/curl test, and a mark-off resistance of about 3.5 or greater.
- 15. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric is coated with a substantially transparent polymer coating.
- 16. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric includes a pattern.
- 17. (withdrawn) A sunscreen according to Claim 16, wherein sald pattern is defined by a printed pattern, an embossed pattern, a thermal pattern or a fluid treatment pattern.
- 18. (withdrawn) A sunscreen according to Claim 7, wherein said knit fabric defines first and second surfaces, and the first surface of the fabric has a visual appearance

Serial No.: 10/810,931 Inventor(s): Masters et al.

U.S. PTO Customer No. 25280

Case No.: 5709

which is different from that of the second surface.

- 19. (withdrawn) A sunscreen according to Claim 7, wherein said fabric and mechanism define a sunscreen in a form selected from the group consisting of roller shades, Roman shades, pleated shades, awnings, cellular shades, vertical blinds, umbrellas, room screens, and dividers.
- 20. (Currently amended) A method of making a sunscreen fabric comprising the steps of:

providing a warp knit fabric having at least a two bar construction, and coating said fabric with a coating comprising a combination of a first urethane polymer having an elongation at break of greater than or equal to 500% and a second urethane polymer having an elongation at break of less than 500%, wherein the ration of the first urethane polymer to said second urethane polymer is about 10:1 on a solids basis.

- 21.(Original) The method according to Claim 20, wherein said fabric has an openness of about 2 to about 25%.
- 22.(Original) The method according to Claim 20, further comprising the step of treating the fabric with a flame retardant.
- 23.(Original) The method according to Claim 20, further comprising the step of dyeing the fabric.
- 24.(Original) The method according to Claim 20, further comprising the step of providing the fabric with a pattern by a process selected from the group consisting of printing, thermal modification, and fluid treatment.
- 25.(Currently amended) The method according to Claim 20, further comprising the step of securing the fabric to a mechanism for securing the fabric to a structure, to thereby form a sunscreen.